

Revised: September 2023

MAINTENANCE GUIDE

Product Range: BRASS FLOORING PROFILES

Material | Solid Brass Grade H/H CZ108 BS2870:EN1652

General:

The installed profile should be swept clean on a daily basis to avoid build up of dust and dirt which may make it more difficult to maintain its appearance.

Immediately after installation and the removal of protective tape, the flooring profile should be wiped with a dry, soft cloth to remove any handling marks and fingerprints.

These brass flooring profiles are produce with a highly polished, satin, antique or chrome plated finish.

Polished Finish:

Highly polished brass profiles require polishing with a suitable metal polish and a soft cloth in order to maintain their appearance. Make sure that all traces of polish are removed during polishing.

Alternatively, profiles can be left to age-oxidise for a natural finish.

Satin Finish:

Wipe with a dry cloth or duster. Do not use any liquids on these finishes.

To remove scuffs and small scratches, a green Scotch pad can be used, rubbing

along the grain of the existing finish.

Antique Finish:

Wipe with a dry cloth or duster. A damp, clean cloth may be used for heavily soiled profiles but must be dried immediately.

Chrome Plated Finish:

Buff occasionally with a dry cloth or duster. A damp, clean cloth may be used for heavily soiled profiles but must be dried immediately.

Important:

AVOID CONTACT WITH WATER AND ALL FORMS OF MOISTURE. PROLONGED CONTACT WITH MOISTURE OR CHEMICALS WILL ACCELERATE THE OXIDISATION PROCESS AND LEAVE MARKS THAT ARE DIFFICULT TO REMOVE WITH NORMAL POLISHING METHODS.

DO NOT USE ABRASIVE MATERIALS, CLEANING AGENTS OR MECHANICAL SCRUBBING DEVICES AS THIS WILL DAMAGE THE SURFACE FINISH.

CARE MUST BE TAKEN TO PROTECT SURROUNDING FLOOR FINISHES DURING MAINTENANCE.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900 email: sales@cat-accs.com website: www.thecatweb.com