




Part of the COBA Group

PRODUCT TECHNICAL DATA SHEET

Revised: August 2023

Catalogue Reference:	AN51/55R BA		
Uniclass2015:	Pr_35_90_31_74 RIGID STAIR NOSINGS		
General Description:	<p>ALUMINIUM STAIR NOSING WITH SLIP RESISTANT PVC INFILL Single Channel/Raked Front. Supplied with Castellated PVC Infill.</p> <p>Infill colour options: Black, White, Light Grey, Flint, Granite, Rustic, Fawn, Ivory, Spruce, Jade, Regency, Mid Blue, Nimbus, Peat, Yellow, Poppy, Claret, Porth Stone, Polar Grey.</p> 		
	<table border="1"> <tr> <td>Castellated Infill SRVs: PTV Dry - 85 PTV Wet - 76</td> </tr> </table>		Castellated Infill SRVs: PTV Dry - 85 PTV Wet - 76
Castellated Infill SRVs: PTV Dry - 85 PTV Wet - 76			
Specifications:	Materials	Profile: Aluminium Alloy 6063 T6 Infill: PVC Compound	
	Tread Dimension	62mm	
	Nosing Dimension	55mm	
	Gauge	5mm	
	Lengths available	Cut to customer sizes up to 2500mm	
	Finish	Black Anodised	
	Drilling	Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill. Drilled for size 8 screws. Fixings not supplied.	
Application:	For abutting to carpet and carpet tiles to finish the nose edge of stairs. Can be rebated to sit flush in wooden steps. Installation guide available.		
Suitability:	For stairs with low to medium traffic volumes. Heavy foot traffic and impact damage can wear through the finish to reveal the natural aluminium colour beneath.		
Additional Information:	Also available with ATI49.5 tread insert for an all-aluminium installation and Olympic Grip carborundum infill for exterior/wet applications.		

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com