




Part of the COBA Group

PRODUCT TECHNICAL DATA SHEET

Revised: June 2022

| | | |
|--------------------------------|--|--|
| Catalogue Reference: | AN51/55R | |
| Uniclass2015: | Pr_35_90_31_74 RIGID STAIR NOSINGS | |
| General Description: | <p>ALUMINIUM STAIR NOSING WITH SLIP RESISTANT INFILL Single Channel/Raked Front. Supplied with Olympic Grip Infill.</p> <p>Infill colour: Black</p> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 10px auto;"> <p>Olympic Grip Infill SRVs: PTV Dry - 92 PTV Wet - 86</p> </div>  | |
| Specifications: | Material | Aluminium Alloy 6063 T6 |
| | Tread Dimension | 62mm |
| | Nosing Dimension | 55mm |
| | Gauge | 5mm |
| | Lengths available | Cut to customer sizes up to 2500mm |
| | Finishes available | Mill Aluminium, Satin Aluminium, Polished Aluminium. |
| | Drilling | <p>Can be supplied pre-drilled and countersunk in the channel for concealed fixing and on-site retro fitting of the infill.</p> <p>Drilled for size 8 screws. Fixings not supplied.</p> |
| Application: | <p>For abutting to carpet and carpet tiles to finish the nose edge of stairs. Can be rebated to sit flush in wooden steps. Compatible with profiles ANE Nap Detail, ANRE25 Ramp Detail and ANEXT extension tread. Installation guide available.</p> | |
| Suitability: | <p>Heavy foot traffic and exterior/wet situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.</p> | |
| Additional Information: | <p>Also available with ATI49.5 tread insert for an all-aluminium installation and Castellated/Smooth Textured PVC infill for interior applications.</p> | |

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com

Manufacturers Of The Finest Specialist Flooring Accessories
www.thecatweb.com