


Catalogue Reference:	KLIKS SLIM TWIN TOP ALUMINIUM WITH BONDED STAINLESS STEEL TOP	
Uniclass2015:	Pr_35_90_31_90 TWO PART FLOOR TRANSITION STRIPS	
General Description:	PROFILE FOR JOINING FLOOR COVERINGS OF THE SAME HEIGHT.	
	<p>Serrated down leg to interlock with KKSBP base profiles. Allows up to 10mm expansion on each side.</p>	
Specifications:	Materials	Base profile: Aluminium Alloy 6063 T6 Bonded top: Stainless Steel Grade 304L
	Visible surface when installed	35mm
	Height adjustment	8mm to 20mm, depending on chosen base
	Compatible bases	KKSBP9.5, KKSBP12, KKSBP15, KKSBP20.
	Lengths available	2000mm, 900mm
	Finish	Brushed Stainless Steel , Bright Stainless Steel
	Standard supply	Undrilled.
	Application:	<p>Installed in combination with one of four compatible bases to protect the edges of the floor coverings. The chosen KKSBP base is firmly affixed to the substrate floor then the top pressed down over it to engage interlock feature between the two profiles. Ideal for finishing timber, ceramic tiles, laminates and any other flooring that requires expansion.</p>
Suitability:	<p>Medium to heavy contract situations such as for use in hotels, pubs, cafes, clubs, commercial offices, shops, schools and public building, as well as for quality domestic installations.</p>	

Post Consumer Recyclability: This product is 100% recyclable at suitable disposal centres.

C.A.T. LTD. Units 24A,B,C Park Avenue Estate, Luton Bedfordshire LU3 3BP. U.K.

T: +44 (0) 1582 561500 F: +44 (0) 1582 561900

email: sales@cat-accs.com

website: www.thecatweb.com